

WD 5 PSV-25/5/22

Technical data		1.628-356.0
EAN code		405427866121
Energy use	W	1100
Rated input power integrated socket	W	min. 100 – max. 2100
Container capacity	l	25
Container material		Stainless steel
Colour		Device head yellow / Device bumper yellow
Power cable	m	5
Standard accessory ID	mm	35
Supply voltage	V / Hz	220 – 240 / 50 – 60
Weight without accessories	kg	8.9
Weight incl. packaging	kg	12
Dimensions (L × W × H)	mm	418 × 382 × 646



WD 5 SV – 25/5/22

Technical data		1.628-356.0
EAN code		405427866189
Energy use	W	1100
Container capacity	l	25
Container material		Stainless steel
Colour		Device head yellow / Device bumper yellow
Power cable	m	5
Standard accessory ID	mm	35
Supply voltage	V / Hz	220 – 240 / 50 – 60
Weight without accessories	kg	8.6
Weight incl. packaging	kg	12
Dimensions (L × W × H)	mm	418 × 382 × 646



WD 6 PSV -30/6/22/T

Technical data		1.628-360.0
EAN code		4054278661810
Energy use	W	1300
Rated input power integrated socket	W	min. 100 – max. 2100
Container capacity	l	30
Container material		Stainless steel
Colour		Device head yellow / Device bumper yellow
Power cable	m	6
Standard accessory ID	mm	35
Supply voltage	V / Hz	220 – 240 / 50 – 60
Weight without accessories	kg	9.3
Weight incl. packaging	kg	13
Dimensions (L × W × H)	mm	418 × 382 × 693



DS 6 *EU

Technical data		1.195-220.0
EAN code		4054278277493
Vacuum Cleaner Type		Water filter vacuum cleaner
Energy efficiency class	A	
Rated input power	W	650
Water filter	l	2
Operating radius	m	10.2
Supply voltage	V / Hz	220 – 240 / 50 – 60
Weight without accessories	kg	7.5
Weight incl. packaging	kg	10.8
Dimensions (L × W × H)	mm	535 × 289 × 345



VACUUM CLEANER

VC 4

Technical data		1.198-640.0
EAN code		4054278834245
Battery powered device		1
Vacuum Cleaner Type		Vacuum cleaner, bagless
Supply voltage	Ph / V / Hz	1 / 100 – 240 / 50 – 60
Sound power level	dB(A)	< 78
Container capacity	ml	650
Battery type		Lithium-ion battery
Voltage	V	21.6
Runtime per battery charging	min	approx. 30
Battery charging time with standard charger	min	345
Power supply for battery charger	V / Hz	220 – 240 / 50 – 60
Weight without accessories	kg	2.4
Weight incl. packaging	kg	4.6
Dimensions (L × W × H)	mm	230 × 236 × 1115



VC 6

Technical data		1.198-680.0
EAN code		4054278834252
Battery powered device		1
Vacuum Cleaner Type		Vacuum cleaner, bagless
Supply voltage	Ph / V / Hz	1 / 100 – 240 / 50 – 60
Sound power level	dB(A)	< 78
Container capacity	ml	800
Battery type		Lithium-ion battery
Voltage	V	25.2
Runtime per battery charging	min	approx. 50
Battery charging time with standard charger	min	235
Power supply for battery charger	V / Hz	220 – 240 / 50 – 60
Weight without accessories	kg	2.6
Weight incl. packaging	kg	6
Dimensions (L × W × H)	mm	235 × 266 × 1130



FLOOR CLEANER

FC 5

Technical data		1.055-400.0
EAN code		4054278516196
Supply voltage	Ph / V / Hz	1 / 220 – 240 / 50 – 60
Rated input power	W	max. 460
Power	W	max. 460
Area performance per tank filling	m²	approx. 60
Tank capacity, fresh water	ml	400
Tank capacity, dirty water	ml	200
Roller working width	mm	300
Floor drying time	min	approx. 2
Cleaning station volume	ml	200
Cable length	m	7
Weight without accessories	kg	4.6
Weight incl. packaging	kg	6.4
Dimensions (L × W × H)	mm	320 × 270 × 1220



FC 5 Premium

Technical data		1.055-460.0
EAN code		4054278516202
Current type	Ph / V / Hz	1 / 220-240 / 50-60
Rated input power / Amps	W	max. 460
Power	W	max. 460
Area performance per tank filling	m²	ca. 60
Fresh water tank capacity	ml	400
Dirty water tank capacity	ml	200
Roller working width	mm	300
Floor drying time	min	ca. 2
Cleaning station volume	ml	200
Cable length	m	7
Weight	kg	4.6
Dimensions (L × W × H)	mm	320 × 270 × 1220



KB 5

Technical data		1.258-400.0
EAN code		4054278208312
Battery powered device		1
Working width of universal brush	mm	210
Container capacity	ml	370
Battery voltage	V	3.7
Battery running time on hard floors	min	30
Battery running time on carpets	min	20
Battery type		Lithium-ion battery
Supply voltage	V / Hz	100 – 240 / 50 – 60
Weight without accessories	kg	1.2
Weight incl. battery	kg	1.2
Weight incl. packaging	kg	1.5
Dimensions (L × W × H)	mm	215 × 230 × 1120



SWEEPERS

S 4 TWIN

Technical data		1.766-360.0
EAN code		4054278247939
Working width with side brush	mm	680
Max. area performance	m²/h	2400
Casing/ frame		Plastic/Plastic
Waste container	l	20
Weight without accessories	kg	10.2
Weight, ready to use	kg	10.2
Weight incl. packaging	kg	11.6
Dimensions (L × W × H)	mm	760 × 668 × 940



KM 70/20 C

Technical data		1.517-106.0
EAN code		4039784718029
Drive type		manual
Max. area performance	m²/h	2800
Working width	mm	480
Working width with 1 side brush	mm	700
Tank volume, gross/net	l	42 / 20
Weight (with accessories)	kg	22
Weight, ready to use	kg	23
Package weight	kg	25.9
Packaging dimensions (L × W × H)	mm	795 / 400 / 935
Dimensions (L × W × H)	mm	1300 / 765 / 1035



SPRAY EXTRACTIONS CLEANER

SE 4001 *EU

Technical data		1.081-130.0
EAN code		4039784254138
Air flow	l/s	70
Vacuum	mbar / kPa	210 / 21
Pump capacity	W	max. 40
Input power turbine/pump	W	1400 / 40
Working width	mm	230
Fresh/waste water tank	l	4 / 4
Standard accessory ID	mm	35
Current type	V / Hz	220 – 240 / 50 – 60
Spray volume	l/min	1
Spray pressure	bar	1
Power cable	m	7.5
Weight without accessories	kg	7.8
Dimensions (L × W × H)	mm	441 × 386 × 480



FLOOR POLISHER

FP 303

Technical data		1.056-820.0
EAN code		4039784195769
Rotational speed	rpm	1000
Rated input power	W	600
Working width	mm	290
Filter bag capacity	l	4
Supply voltage	V / Hz	220 – 240 / 50 – 60
Weight without accessories	kg	6.6
Weight incl. packaging	kg	8
Dimensions (L × W × H)	mm	385 × 339 × 1162



Please contact us for more information:

Ahmedabad Regus Business Centre, Office No-314, East Wing B Wing Privilon, 3rd Floor, S.G. Highway, Ahmedabad-380 054 Gujarat	Hyderabad Office No 446,448,449, 1-10-39 to 44, Level 4-5, Gumidell, Commercial Complex, Old Airport Road, Begampet, Hyderabad-560 016, Telangana	Kochi Office 5-45, 8th Floor Allapet Heritage Building Mahatma Gandhi Road, Noth end Kochi-682 035, Kerala	Noida A-42/4, Sector-62 Noida-201 309, Uttar Pradesh
Bengaluru 504 Stage, 4th Block, 1st, 100ft Outer Ring Road (Service Road), HBR Layout (Near Vijaya Bank), Bangalore-560 043, Karnataka	Indore 903, Apollo Premier, 9th Floor, Plot No. 1, Scheme PU-4, Vijay Nagar, Indore-452 010, Madhya Pradesh	Kolkata 4th Floor, Shree Manjari Building, 8/1A, Sir William Jones Sarani Kolkata-700071, West Bengal	Pune Regus Platinum Towers Office No. 836, 8th Floor 1 Naylor Road, Pune-411001, Maharashtra
Chandigarh Office No-433, Level-4, Tower A, Godrej eternia, Plot number 70, Industrial Area Phase-1 Chandigarh-160 002	Jaipur Office NO.605, 6th floor, Tonk Road & 82 Bypass Junction, Sector B-4, Near Airport, Jaipur-302018, Rajasthan	Mumbai A 206 & B 009, Punit Industrial Estate, TTC industrial Area, Thane Belapur Road, Turbbhe, Navi Mumbai-400 705, Maharashtra	Vadodara CS, 3rd Floor, Alembic 1965, Alembic City, Gorwa-Alembic Road, Vadodara 390 003, Gujarat
Chennai No. 54, Alappakkam Main Road, Maduravoyal, Chennai 600 095	Jamshedpur Offie No JSP-01 Fair deal Complex, 1st Floor, Main Road, Bistupur, Jamshedpur-831.001, Jharkhand		

KÄRCHER

makes a difference

Designed and engineered
by Kärcher in Germany



CORDLESS WINDOW VACUUM

WV 1 Plus *EU

Technical data		1.633-914.0
EAN code		4054278229171
Working width of vacuum nozzle		250
Dirty water tank capacity	ml	100
Battery running time	min	20
Battery charging time	min	185
Cleaning performance per battery charge		Approx. 55 m² = 18 windows
Battery type		Lithium-ion battery
Current type	V / Hz	100-240 / 50-60
Weight incl. battery	kg	0.5
Dimensions (L × W × H)	mm	130 × 250 × 275



Facebook



Instagram



Linkedin



Twitter



Yr utube

🌐 : www.kaercher.com/in

✉ : marketing.in@kaercher.com

☎ : 1800 1234 180



HIGH PRESSURE WASHERS

K 1 HORIZONTAL

Technical data		1.599-101.0
EAN code	4054278644493	
Supply voltage	V / Hz	220 ~ 240 / 50 ~ 60
Pressure	bar	max. 100
Flow rate	l/h	270 ~ 300
Inlet temperature	°C	max. 40
Connection load	kW	1.2
Power cable	m	5
Weight without accessories	kg	4.1
Weight incl. packaging	kg	5.6
Dimensions (L × W × H)	mm	384.5 × 174 × 298



K 2 HORIZONTAL

Technical data		1.599-151.0
EAN code	4054278644486	
Supply voltage	V / Hz	220 ~ 240 / 50 ~ 60
Pressure	bar	max. 110
Flow rate	l/h	300 ~ 360
Inlet temperature	°C	max. 40
Connection load	kW	1.4
Weight without accessories	kg	4.7
Weight incl. packaging	kg	6.6
Dimensions (L × W × H)	mm	499.5 × 174 × 305.5



K 2.350

Technical data		1.601-685.0
EAN code	4039784509856	
Supply voltage	V / Hz	220 ~ 240 / 50 ~ 60
Pressure	bar / MPa	max. 110 / max. 11
Flow rate	l/h	max. 360
Inlet temperature	°C	max. 40
Weight without accessories	kg	5.7
Weight incl. packaging	kg	7.4
Dimensions (L × W × H)	mm	328 × 258 × 661



K 4 COMPACT

Technical data		1.637-300.0
EAN code	4054278497150	
Supply voltage	V / Hz	230 / 50
Pressure	bar	20 ~ max. 130
Flow rate	l/h	420
Area performance	m²/h	30
Inlet temperature	°C	max. 40
Connection load	kW	1.8
Weight without accessories	kg	11
Weight incl. packaging	kg	13.9
Dimensions (L × W × H)	mm	348 × 308 × 520



K 5 COMPACT

Technical data		1.630-750.0
EAN code	4054278498041	
Supply voltage	V / Hz	230 / 50
Pressure	bar / MPa	20 ~ up to 160 / 2 ~ max. 14.5
Flow rate	l/h	max. 500
Area performance	m²/h	40
Inlet temperature	°C	max. 40
Connection load	kW	2.1
Power cable	m	5
Weight without accessories	kg	12
Weight incl. packaging	kg	15.2
Dimensions (L × W × H)	mm	354 × 308 × 520



K 7

Technical data		1.168-502.0
EAN code	4039784720237	
Supply voltage	V / Hz	230 / 50
Pressure	bar / MPa	20 ~ up to 160 / 2 ~ max. 16
Flow rate	l/h	max. 600
Area performance	m²/h	60
Inlet temperature	°C	max. 60
Connection load	kW	3
Power cable	m	5
Weight without accessories	kg	18.9
Weight incl. packaging	kg	23.8
Dimensions (L × W × H)	mm	404 × 461 × 968



STEAM CLEANERS

SC2 EASY FIX

Technical data		1.512-950.0
EAN code	4054278312491	
Test certificate*	Kills up to 99.999% of coronavirus** and 99.99% bacteria**	
Area performance per tank filling	m²	approx. 75
Heating output	W	1500
Max. steam pressure	bar	max. 3.2
Cable length	m	4
Heat-up time	min	6.5
Boiler/tank capacity	l	1
Supply voltage	Ph / V / Hz	1 / 220 ~ 240 / 50 ~ 60
Weight without accessories	kg	2.9
Weight incl. packaging	kg	4.5
Dimensions (L × W × H)	mm	380 × 254 × 260



SC4 EASY FIX

Technical data		1.512-450.0
EAN code	4054278313023	
Test certificate*	Kills up to 99.999% of coronavirus** and 99.99% bacteria**	
Area performance per tank filling	m²	approx. 100
Heating output	W	2000
Max. steam pressure	bar	max. 3.5
Cable length	m	4
Heat-up time	min	4
Boiler/tank capacity	l	0.5 / 0.8 (removable tank)
Supply voltage	Ph / V / Hz	1 / 220 ~ 240 / 50 ~ 60
Weight without accessories	kg	4.1
Weight incl. packaging	kg	5.7
Dimensions (L × W × H)	mm	380 × 251 × 273



SC 5 EASY FIX

Technical data		1.512-430.0
EAN code	4054278309484	
Test certificate*	Kills up to 99.999% of coronavirus** and 99.99% bacteria**	
Area performance per tank filling	m²	approx. 150
Heating output	W	2200
Max. steam pressure	bar	max. 4.2
Cable length	m	6
Heat-up time	min	3
Boiler/tank capacity	l	0.5 / 1.5 (removable tank)
Supply voltage	Ph / V / Hz	1 / 220 ~ 240 / 50
Weight without accessories	kg	6
Weight incl. packaging	kg	8.8
Dimensions (L × W × H)	mm	439 × 301 × 305



SV 7

Technical data		data 1.439-419.0
EAN code	4039784998858	
Max. performance	W	2200
Water capacity boiler	l	0.45
Refill tank	l	0.5
Max. steam pressure	bar	max. 4
Water filter	l	1.2
Vacuum	mbar / kPa	210 / 21
Cable length	m	6
Heat-up time	min	5
Steam flow rate	gh	65
Filter system	Multi-stage filter system	
Heating output	W	1100
Permanent filling	l	1
Additional suction capacity	l	0.6
Weight without accessories	kg	9.4
Weight incl. packaging	kg	15.6
Dimensions (L × W × H)	mm	515 × 336 × 340



WET & DRY VACUUM CLEANERS

WD 1 CLASSIC

Technical data		1.098-322.0
EAN code	4054278827872	
Actual suction power*	Air watts	180
Container capacity	l	15
Container material	Plastic	
Power cable	m	5
Standard accessory ID	mm	35
Supply voltage	V / Hz	220 ~ 240 / 50 ~ 60
Weight without accessories	kg	3.9
Weight incl. packaging	kg	5.8
Dimensions (L × W × H)	mm	331 × 352 × 462



WD 1s Classic

Technical data		1.098-322.0
EAN code	4054278827889	
Actual suction power*	Air watts	200
Container capacity	l	18
Container material	Stainless steel	
Power cable	m	5
Standard accessory ID	mm	35
Supply voltage	V / Hz	220 ~ 240 / 50 ~ 60
Weight without accessories	kg	4.7
Weight incl. packaging	kg	7
Dimensions (L × W × H)	mm	398.6 × 398.6 × 518.8



WD 2 Plus -15/4/18

Technical data		1.628-850.0
EAN code	4054278658021	
Energy use	W	1000
Container capacity	l	15
Container material	Stainless steel	
Colour	Device head yellow / Device bumper yellow	
Power cable	m	4
Standard accessory ID	mm	35
Supply voltage	V / Hz	220 ~ 240 / 50 ~ 60
Weight without accessories	kg	4.5
Weight incl. packaging	kg	6.2
Dimensions (L × W × H)	mm	353 × 328 × 431



WD 2 PLUS S V- 15/4/18

Technical data		1.628-903.0
EAN code	4054278655673	
Energy use	W	1000
Container capacity	l	15
Container material	Plastic	
Colour	Device head yellow / Device bumper yellow / Container yellow	
Power cable	m	4
Standard accessory ID	mm	35
Supply voltage	V / Hz	220 ~ 240 / 50 ~ 60
Weight without accessories	kg	4.3
Weight incl. packaging	kg	6
Dimensions (L × W × H)	mm	349 × 328 × 430



WD3 SV-19/4/20

Technical data		1.628-141.0
EAN code	4054278656311	
Energy use	W	1000
Container capacity	l	19
Container material	Stainless steel	
Colour	Device head yellow / Device bumper yellow	
Power cable	m	4
Standard accessory ID	mm	35
Supply voltage	V / Hz	220 ~ 240 / 50 ~ 60
Weight without accessories	kg	4.9
Weight incl. packaging	kg	7
Dimensions (L × W × H)	mm	353 × 328 × 523



WD 3 V-19/4/20

Technical data		1.628-107.0
EAN code	4054278656083	
Energy use	W	1000
Container capacity	l	19
Container material	Plastic	
Colour	Device head yellow / Device bumper yellow / Container yellow	
Power cable	m	4
Standard accessory ID	mm	35
Supply voltage	V / Hz	220 ~ 240 / 50 ~ 60
Weight without accessories	kg	4.7
Weight incl. packaging	kg	6.4
Dimensions (L × W × H)	mm	349 × 328 × 528



WD 4 SV-20/5/22

Technical data		1.628-250.0
EAN code	4054278661841	
Energy use	W	1000
Container capacity	l	20
Container material	Stainless steel	
Colour	Device head yellow / Device bumper yellow	
Power cable	m	5
Standard accessory ID	mm	35
Supply voltage	V / Hz	220 ~ 240 / 50 ~ 60
Weight without accessories	kg	7.2
Weight incl. packaging	kg	10.2
Dimensions (L × W × H)	mm	384 × 365 × 524



WD 4 SV-20/6/22 CAR

Technical data		1.628-259.0
EAN code	4054278676542	
Energy use	W	1000
Container capacity	l	20
Container material	Stainless steel	
Colour	Device head yellow / Device bumper yellow	
Power cable	m	6
Standard accessory ID	mm	35
Supply voltage	V / Hz	220 ~ 240 / 50 ~ 60
Weight without accessories	kg	7.2
Weight incl. packaging	kg	10
Dimensions (L × W × H)	mm	384 × 365 × 524



WD 4 V-20/4/35

Technical data		1.628-204.0
EAN code	4054278661896	
Energy use	W	1000
Container capacity	l	20
Container material	Plastic	
Colour	Device head yellow / Device bumper yellow / Container yellow	
Power cable	m	4
Standard accessory ID	mm	35
Supply voltage	V / Hz	220 ~ 240 / 50 ~ 60
Weight without accessories	kg	6.8
Weight incl. packaging	kg	10
Dimensions (L × W × H)	mm	384 × 365 × 526



WD 4 V- 20/6/22 CAR

Technical data		1.628-208.0
EAN code	4054278661896	
Energy use	W	1000
Container capacity	l	20
Container material	Plastic	
Colour	Device head yellow / Device bumper yellow / Container yellow	
Power cable	m	4
Standard accessory ID	mm	35
Supply voltage	V / Hz	220 ~ 240 / 50 ~ 60
Weight without accessories	kg	6.8
Weight incl. packaging	kg	10
Dimensions (L × W × H)	mm	384 × 365 × 526



WD 5PV -25/5/22

Technical data		1.628-306.0
EAN code	4054278662114	
Energy use	W	1100
Rated input power integrated socket	W	min. 100 ~ max. 2100
Container capacity	l	25
Container material	Plastic	
Colour	Device head yellow / Device bumper yellow / Container yellow	
Power cable	m	5
Standard accessory ID	mm	35
Supply voltage	V / Hz	220 ~ 240 / 50 ~ 60
Weight without accessories	kg	8.4
Weight incl. packaging	kg	12.2
Dimensions (L × W × H)	mm	418 × 382 × 653

